

## **Overview**

## Maintain the printer's reliability and quality

Maintain consistent print quality and system uptime with the easy to install 110-volt fuser. Ensure reliable paper picking by refreshing your pick rollers.

Keep print quality consistent and increase uptime

Keep the printer running smoothly

Get reliable paper picking

## **Specifications**

Print Technology	Laser
Operating temperature range	15 to 32.5ºC
Storage temperature range	-30 to 60ºC
Operating humidity range	10 to 80% RH
Non-Operating Humidity Range	10 to 90% RH
Compatibility	HP LaserJet Enterprise M607n K0Q14A, HP LaserJet Enterprise M607dn K0Q15A, HP LaserJet Enterprise M608n K0Q17A, HP LaserJet Enterprise M608dn K0Q18A, HP LaserJet Enterprise M608x K0Q19A, HP LaserJet Enterprise M609dn K0Q21A, HP LaserJet Enterprise M609dh K0Q20A, HP LaserJet Enterprise M609x K0Q22A, HP LaserJet Managed E60055dn M0P33A, HP LaserJet Managed E60065dn M0P35A, HP LaserJet Managed E60065x M0P36A, HP LaserJet Managed E60075dn M0P39A, HP LaserJet Managed E60075x M0P40A
Quantity per pallet	100
UPC number	889894213532
Minimum dimensions (W x D x H)	365 x 143 x 106 mm
Minimum dimensions (W x D x H)	14.4 x 5.6 x 4.2 in (Replacement parts only; no shipping material)
Package dimensions (W x D x H)	498 x 238 x 239 mm
Package dimensions (W x D x H)	19.6 x 9.37 x 9.41 in
Pallet dimensions (W x D x H)	1200 x 1000 x 2399 mm
Pallet dimensions	47.2 x 39.37 x 94.44 in
Package weight	3 kg
Package weight	6.6 lb
Pallet weight	300 kg
Pallet weight	661.3 lb
Page yield (black and white)	Up to 225,000 pages
What's in the box	Fuser unit (110V); Documentation (Hardware Install Guide, Recycle Guide)
Warranty	90 Day HP Dealer Exchange. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region.

## **Additional specifications**

Count of cartons per pallet layer	10
Count of layers in pallet	10
Country of origin	Made in China
Electromagnetic compatibility	CISPR 22:2008 (International) - Class A, CISPR 32:2012 (International) - Class A, EN 55032: 2012 (EU) - Class A, EN 61000-3-2: 2014 (EU), EN 61000-3-3: 2013 (EU), EN 55024: 2010 (EU), EMC Directive 2014/30/EU, FCC CFR 47 Part 15 Class A / ICES-003, Issue 6 Class A (US/Canada). Other EMC approvals as required by individual countries
Operating temperature range	15 to 32.5ºC
Orderable product number	L0H24A
Page yield (color)	Up to 225,000 pages
Print technology	Laser
Product subgroup	Fuser/Maintenance Kits
Safety	IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); Low Voltage Directive 2014/35/EU with CE Mark (Europe); Other safety approvals as required by individual countries
Smaller master carton barcode	#BLANK##
Storage temperature range	-22 to 140ºF
Sub-brand name	LaserJet
Tariff numbers	8443992550 (AM-Base-HTS); 8443999000 (EU-Base-HTS); 84439990 (AP-Base-HTS)
UNSPSC code	44103116
Warranty	90 Day HP Dealer Exchange. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region.
Weight	1.7 kg
Weight	3.4 lb (Replacement parts only; no shipping material)

Generated by Dynamic Collateral Tool – (ww-en) – Mar 22, 2019 6:05 AM UTC+0000